B-1	Bridge Condition Attachr	nent PERMIT #
COMP	ANY BILLED: Haulers Name	LOAD: <i>Hay</i>
① N	k② k THE BOXES BELOW DEPICT A SIDE VIEV	Truck & (2) axle trailer OF YOUR TRACTOR-TRAILER COMBINATION OR VEHICLE. IDS TO THE AXLE(S) & AXLE GROUPS IN YOUR CONFIGURATION. N NON-STANDARD & MARK AN "L" FOR ANY LIFT AXLES IN THE DRIVE GROUP)
STEERIN	NG AXLE(S) NG AXLE(S) DRIVE GROUP	X X X BOOSTER BOOS
<u> </u>	MARK SPACINGS (distance in	FEET or INCHES) BETWEEN EACH & EVERY AXLE SHOWN
	13.2k 38k	FOR EACH AXLE OR AXLE GROUP (1k = 1,000 pounds(#))
-		11" WIDTH (NOMINAL) IN INCHES (0.0394 X mm = inches)
	•	EXCEED: 750#/IN FOR MOVES > 50 MILES, 800#/IN FOR MOVES > 25 MILES, 900#/IN FOR MOVES > 15 MILES)
A	CTUAL COMBINED VEHICLE WEIGHT: 9	2.2k LEGAL COMBINED VEHICLE WEIGHT:(BRIDGE FORMULA/AXLES)
LIFT AXLE(S) MUST REMAIN DOWN IN LOAD-CARRYING POSITION AT ALL TIMES, UNLESS OTHERWISE NOTED. DRIVE GROUPS WEIGHING OVER 70K MUST HAVE 12 TIRES ON 3-AXLE GROUPS & 14 TIRES ON 4-AXLE GROUPS. GENERAL & SPECIAL BRIDGE CONDITIONS		
Ger	neral Conditions: CROSS <u>ALL</u> BRIDGES AT A C	ONSTANT SPEED WITH NO BRAKING, SHIFTING, OR ACCELERATING.
1. LII 2. IM 3. St 4. PI 5. No	raddle bridge centerline while crossing (extra flag ace one of vehicle wheel lines on bridge centerlin b other vehicles allowed on bridge at same time a introl at both ends of bridge). b NOT cross bridge. MUST USE ON/OFF RAMPS To	a constant speed not to exceed 3 MPH while following a walking flagperson. berson(s) required for traffic control on 2-lane roads). while crossing. this overweight vehicle while crossing (extra flagpersons required for traffic
	•	SPECIAL BRIDGE CONDITIONS
	E LOCATION	(from above list)
	see Bridge Continuation Attachment (B-2) for additional lastisblanksjow_overweight.doc as of: 9/21/2011 11:40:00 AM	ridge conditions. Reviewed by: