

13188

WATER WELL DRILLING LOG
BRANDS WELL DRILLING
Box 33, Fairbanks

TO 100' HILL
Aug 25-82
USGS No.

Driller Richard H. Brand

Area

Well Owner Richard Brand

Use of Well WPS

Location (address of: Township, Range and Section, if known; or distance from main road:

1 Mile CHS Rd - below road, behind GUEA Sub Station

Size of Casing 3" Depth of Hole 115' feet. Cased to 115' feet.

Static water level 5 feet (above) (below) land surface. Finish of well (check one)

Open end (☒) Screen (☐); Perforated (☒)

Describe screen or perforations 2" casing shoe to 99.4' - 21' x 2" gen liner to 115' 1/4 holes

Well pumping test at 25 gallons per (hour) (minute) for 1 hours with Gas driven surface pump

Amount of drawdown from static level

Remarks Water cleaned up in 15 min of pumping

WELL LOG

Depth in feet from ground surface Give details of formations penetrated, size of material, color, and hardness.

0	to	6'	Dry silt
6'	to	25'	Wet " "
25'	to	55'	" " Drive casing to 60'
55'	to	99'	" " with soft brown rock + quartz - Shoe to 99.4
99	to	115'	brown med hard rock + quartz lots of water 25 to 40 GPM
	to		Drive 21' x 2" perforated liner to 115' cleaned out
	to		water cleaned up in 10 min of blowing with air.

ADLWM LK LAS 6767

NW 1/4 SE 1/4 NE 1/4 SE 1/4 S12 29, T. 1N, R. 2E, FM

FA 1-2-29 DAD