

*Guide for Using the Hydrogeologic Classification System for Logging Water Well Boreholes by Thomas M. Hanna NGWA Press

HARTNER DRILLING

BIG LAKE, SR BOX 2603, WASILLA, ALASKA 99687

892-6273

20648
DO NOT FILL IN

USGS No. _____

Area _____

Driller Jim Hartner

Well Owner Jim Julian Use of Well residential

Location (address of: Township, Range, and Section, if known, or distance from main road:

Ranchette Subdivision, Block 3, Lot #16, Big Lake, Alaska

Date Completed 11-10-78

Size of casing 6" Depth of hole 53 feet.

Cased to 50 feet. Static water level _____ feet ~~XXXXX~~ (below) land surface.

Finish of Well (check one) Open End ☒ Screen ☐ or Perforated ☐. Description of screen or perforation:

Well pumping test at 30 gallons per ~~XXXX~~ (minute) for 2 (hours) ~~XXXX~~ (minutes) with

_____ feet drawdown from static level.

Remarks: 1 Drive shoe in well.

WELL LOG

Depth in feet from ground surface	Give details of formations penetrated, size of material, color, and hardness.
0 to 1.5 ft.	Organic material
1.5 to 25	4" minus gravel, some sand, small amount of silt
25 to 31	4" minus gravel, some sand, small amount of silt, and approximately 12 gallons per minute of water.
31 to 46	Silt, 3" minus gravel, small amount of sand.
46 to 53	2" minus gravel, small amount of silt, some sand, and approximately 30 gallons per minute of water.
_____ to _____	_____
_____ to _____	_____
_____ to _____	_____
_____ to _____	_____
_____ to _____	_____
_____ to _____	_____
_____ to _____	_____

Pl 11/18
CR-F 382

Accy to Bank - 11/10/78

SB 17-3-22