

*Guide for Using the Hydrogeologic Classification System for Logging Water Well Boreholes by Thomas M. Hanna NGWA Press

Alyeska

PUMP STATION # 6

25092

8"Ø-460' and 7"

Ø of Casing: 460-800' Depth of Hole: 800' - Cased to 800 feet.

Static Water Level: 606 feet (~~xxxxx~~) (below) land surface. Finish of well (check one): () Open End; () Screen; (x) Perforated.

Describe screen or perforations: Torch cut perforated casing 600' - 800'

Well pumping test at 30 gallons per (~~hour~~) (minute) for 24 hours, with 0 feet of drawdown from static level.

Drilled By: Alaska Diamond Drillers

Date Completed: July, 1976.

Depth in feet from ground surface	Give details of formations penetrated, size of material, color and hardness:
<u>0</u> to <u>78</u>	<u>Permafrost.</u>
<u>78</u> to <u>275</u>	<u>Sand and shale.</u>
<u>275</u> to <u>325</u>	<u>Rock.</u>
<u>325</u> to <u>570</u>	<u>Rock and shale.</u>
<u>570</u> to <u>649</u>	<u>Rock.</u>
<u>649</u> to <u>744</u>	<u>Shale.</u>
<u>744</u> to <u>800</u>	<u>Rock and shale.</u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>
<u> </u> to <u> </u>	<u> </u>

PS 6 on site well

LAS 6660

FB 13-1-26 CC