



# Kraxberger Drilling Co. Well Drilling Log

Well owner: Soldotna city

Driller: BRK

Completion: 4/27/00

Builder: Jeff Cobol

City: Soldotna

Road/Area: Spur Hwy/Karen St

Legal 1: \_\_\_\_\_

Legal2: page 1

Depth: <u>457</u>	Casing length: <u>457</u>	Diameter: <u>6</u>	Rig type: <u>RR</u>
Static level: <u>122</u>	Yield/GPM <u>300.</u>	Finish of well: <u>screen 195-265</u>	

0-3 gravel pad

5-12 clay

34-41 sand

72-94 sand

101-120 gray clay

125-127 gray clay

137-140 cemented grv & rock

194-203 sand,grv,water(50-75g

---

305-310 clay

313-317 clay

3-5 sand & clay

12-34 rocky clay

41-72 rocky clay

94-101 silty sand

120-125 wet sand

127-137 sand,grv,water(3gpm)

140-194 gray rocky clay

203-305 san,grv,rocks,water,

coal,wood (static 144)

310-313 sand,silt,water

317-350 silt,coal,sand,water

# Kraxberger Drilling Co. Well Drilling Log

Well owner: Soldotna City

Driller: BRK

Completion: 4/27/00

Builder: Jeff Cobol

City: Soldotna

Road/Area: Kenai Spur/Karen St By water Tanks

Legal 1: \_\_\_\_\_

Legal2: page 2

Depth: <u>457</u>	Casing length: <u>457</u>	Diameter: <u>6</u>	Rig type: <u>AR</u>
Static level: <u>122</u>	Yield/GPM <u>300.</u>	Finish of well: <u>screen 195-265</u>	

350-370 cleaner sand, coal, wate

435-457 coarser sand, grv, wood

(Grouted 20')

100 slot screen 200-205

.010 screen 220-265

(cut casing 270' backfilled with

(total screen length 74'2")

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_



370-435 sand, silt, coal, wood, wat

coal (brown tint to sand)

130slot screen 195-200

.012 screen 205-220

(Test pumped 29 hrs)

washed gravel)

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_