





# WELL PIPING MODIFICATION DETAIL

N.T.S.

NOTES:  
ALL STAINLESS FITTING TYPE 304 S.S.  
DRILL 2 EA. 1 1/4" HOLES ON TOP OF  
EL. PRIOR TO WELDING COUPLINGS

*Brewig Mission 340A18*

## WELL DATA

DRILLER: ROY E. LONGBOTHAM, JR

	WELL W-00-2	WELL W-00-3
DATE COMPLETED	JULY 28, 2000	AUGUST 8, 2000
STATIC WATER LEVEL	14 FT. BELOW LAND SURFACE	10.8 FT. BELOW LAND SURFACE
TEST PUMPED	75 GPM FOR 15 HRS WITH 2 FT. OF DRAWDOWN	75 GPM FOR 15 HRS WITH 1.5 FT OF DRAWDOWN
DRILLERS LOG	0-5' LIGHT BROWN CLAY AND ROCKS 5'-24.5' FROZEN LIGHT BROWN CLAY, ROCKS AND GRAVEL 24.5'-42' FROZEN BLUE CLAY AND SOME ROCK 42'-48.5' FROZEN YELLOW CLAY AND GRAVEL 48.5'-52' (WATER) GRAVEL, SOME SAND 52'-53' FROZEN CLAY, NO WATER	0-5' LIGHT BROWN CLAY AND ROCKS 5'-29' FROZEN LIGHT BROWN CLAY AND ROCKS 29'-35' FROZEN YELLOW CLAY AND ROCKS 35'-41' FROZEN LIGHT BROWN CLAY AND ROCKS 41'-50' WATER IN COARSE GRAVEL AND SAND 50'-51' REAL MUCKY FINE SAND, NO WATER

OPER  
ENTER  
DATE

REVISION	BY	DATE

Project No. \_\_\_\_\_  
 Date JAN 2001  
 Designed KRH

Sheet No. C-2  
 SHEET 7